

EXPLODED DRAWING

JAM² SL

PP2302 | C-C

| POS | PART # | PART NAME | QTY |
|-----|-------------|---|-----|
| 01 | KD325923995 | LINKAGE KIT: MAINLINK & SHOCK EXTENSION | 1 |
| 02 | KD325923994 | PIVOT KIT: ALL SCREWS, WASHERS & SPACERS | 1 |
| 03 | KD325923996 | SEALING KIT: ALL BEARING SEALINGS | 1 |
| 04 | KD325923039 | BATTERY MOUNT NUT 01 (THREADED FOR BOTTLECAGE MOUNT) | 1 |
| 05 | KD325923040 | BATTERY MOUNT NUT 02 (SLOTTED FOR RANGE EXTENDER) | 1 |
| 06 | KD325923041 | BATTERY MOUNT NUT 03 | 1 |
| 07 | KD325923998 | BEARING KIT: 8X 61801 2RSR, 4X 61901 2RSR, 2X 61902 2RSR | 1 |
| 08 | KD325920052 | SEATSTAY PROTECTOR | 1 |
| 09 | KD325923053 | CHAINSTAY PROTECTOR | 1 |
| 10 | KD325923054 | MOTOR COVER | 1 |
| 11 | KD325923055 | DOWNTUBE PROTECTOR | 1 |
| 12 | KD325923056 | BATTERY COVER | 1 |
| 13 | KD325923057 | CHAINGUIDE SET | 1 |
| 14 | KD325923058 | SPLASH GUARD | 1 |
| 15 | KD325923059 | SPEED SENSOR HOLDER | 1 |

| | | | |
|----|-------------|---------------------------|---|
| 16 | KD325923060 | LOCK PLATE | 1 |
| 17 | KD199123008 | SCREW M5X10 DIN912 | 2 |
| 18 | KD199123009 | SCREW M5X12 DIN912 | 2 |
| 19 | KD199123011 | WASHER M5 DIN125 | 4 |
| 20 | KD199123021 | SCREW M4X8 DIN912 | 4 |
| 21 | KD199123007 | SCREW M3X10 ISO7380-2 | 5 |
| 22 | KD199123020 | SCREW M5X20 TX ISO14583 | 1 |
| 23 | SRAM PART | SRAM UDH HANGER | 1 |
| 24 | KD160221010 | FOCUS THRUAXLE SH-173 | 1 |
| 25 | KD199119008 | BOTTLECAGE SCREW M5X12 | 3 |
| 26 | KD325923081 | RUBBER PLUG | 1 |
| 27 | KD170520003 | SPEED MAGNET | 1 |
| 28 | KD325923086 | FRAME PROTECTION STICKERS | 1 |

| | |
|------------------------|---|
| MATERIAL | CARBON - CARBON |
| WHEELSIZE | 29" / 15 X 110 - 29" / 12 X 148 / MAX TIRE 66 MM |
| TRAVEL | FRONT 160 MM - REAR 150 MM |
| SHOCK | LENGTH 210 MM - STROKE 55 MM - HARDWARE 25X8 MM / NO HARDWARE |
| HEADSET | ACROS ANGLE ADJUSTMENT HEADSET UPPER 0,6° / Ø56 MM - LOWER 0,6° / Ø56 MM |
| FORK | 29" - LENGTH 571 MM - RAKE 44 MM |
| SEATPOST / SEATCLAMP | Ø31,6 MM - Ø35,5 MM - MINIMUM INSERT 100 MM |
| MAX SEATPOST INSERTION | S: 220 MM M: 250 MM L: 270 MM XL: 290 MM |
| REAR BRAKEMOUNT | POSTMOUNT Ø180 MM - MAX. ROTOR Ø203 MM |
| REAR AXLE | 173 MM / Ø12 MM / PITCH 1,0 |
| RD HANGER | SRAM UDH |
| CHAINGUIDE MOUNT | FOCUS DIRECT MOUNT |
| CHAINRING | MIN CHAINRING SIZE: 32 / MAX CHAINRING SIZE: 34 / CHAINLINE: 95 MM |
| KICK STAND MOUNT | - |
| MOTOR | FAZUA RIDE 60 |
| BATTERY | FAZUA 430 WH / RANGE EXTENDER 180 WH |
| REAR SHOCK SAG | SAG IN %: 30 / SAG IN MM: 16,5 |
| MAX SYSTEM WEIGHT | 135KG |

