



## CRAFTY CARBON RR SL

Carrera Blue / Black / Crystal White

- Also available as frameset



**FRAME** STEALTH AIR FULL CARBON • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT600Wh, 250Wh POWERMORE OPTIONAL • **FORK** FOX 36 GRIP X2 FACTORY, 160mm • **REAR SHOCK** FOX FLOAT X FACTORY EVOL • **SEATPOST** ROCKSHOX REVERB AXS • **BRAKES** SRAM CODE ULTIMATE STEALTH • **WHEELS** e\*THIRTEEN SYLVAN RACE CARBON • **REAR DERAILLEUR** SRAM XX EAGLE AXS T-TYPE



## e-MTB ENDURO / CRAFTY CARBON RR SL

Carrera Blue / Black / Crystal White

<b>FRAME</b>	Crafty Stealth Air full Carbon, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm
<b>REAR SHOCK</b>	Fox Float Factory Kashima EVOL 185x55mm. Settings: Settings: 2-position compression (Open/Firm), rebound, air preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	CM compression, SCLRM5.2 rebound, CML, 0.2 volume spacer
<b>FORK</b>	Fox 36 29 Float GRIPX2 Factory Kashima, 160mm, tapered steerer tube, Boost 15x110mm Kabolt axle, 44mm offset. Settings: high and low-speed compression, high and low-speed rebound, air preload
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Acros custom ZS56/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock
<b>STEM</b>	Onoff S9 30mm 0°. Full CNC, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff S9 1.0 Carbon, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise
<b>GRIPS</b>	Onoff Desert Pro, CNC lock-on, 135mm. L and XL: Thicker size
<b>SEATPOST</b>	RockShox Reverb Stealth AXS, diameter 31.6mm S size: 340x125mm, M size: 390x150mm, ML size: 440x170mm, L size: 440x170mm, XL size: 440x170mm
<b>SADDLE</b>	FIZIK Vento Argo 00 Carbon 150mm
<b>FRONT BRAKE</b>	Sram Code Ultimate Stealth, oversized 4-piston caliper, HS2 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>REAR BRAKE</b>	Sram Code Ultimate Stealth, oversized 4-piston caliper, HS2 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>BRAKE LEVER</b>	Sram Code Ultimate Stealth, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
<b>RIMS</b>	e*thirteen Sylvan Race Carbon IW30, Hookless carbon rim, 30mm internal width, tubeless ready, 28 spokes
<b>SPOKES</b>	e*thirteen custom Hive triple-buttet black steel, alloy nipples, nipple washers

<b>FRONT HUB</b>	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
<b>REAR HUB</b>	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub
<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.5, tubeless ready, 3C MAXX GRIP, EXO+ Protection, 600TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.5 tubeless ready, 3C MAXX TERRA, EXO+ Protection, 60TPI, folding bead
<b>CRANKSET</b>	E.13 Helix Race Carbon E*Spec Plus, All sizes: 160mm
<b>RINGS</b>	Sram T-Type 34T, steel, narrow-wide, 104 BCD
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Sram XX Eagle T-Type, 12s, Powerlock
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Sram XX Eagle AXS, T-Type, 12s
<b>SHIFT LEVERS</b>	Sram Eagle AXS Pod MMX, 12s
<b>CASSETTE</b>	Sram XS-1295, 10-52T, T-Type, 12s
<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BATTERY</b>	Bosch Powertube 600Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	--
<b>OTHERS</b>	--
<b>WEIGHT</b>	--



## CRAFTY CARBON XR

Mars / Black



**FRAME** STEALTH AIR FULL CARBON • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT600Wh, 250Wh POWERMORE OPTIONAL • **FORK** ÖHLINS RXF 38, 170mm • **REAR SHOCK** ÖHLINS TTX22 M.2 COIL • **SEATPOST** ONOFF PIJA ADJUSTABLE LENGTH • **BRAKES** SRAM MAVEN SILVER • **WHEELS** MAVIC E-DEEMAX S • **REAR DERAILLEUR** SRAM XO EAGLE AXS T-TYPE



## e-MTB ENDURO / CRAFTY CARBON XR

Mars / Black

<b>FRAME</b>	Crafty Stealth Air full Carbon, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm
<b>REAR SHOCK</b>	Öhlins TTX22M.2 185x55mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	C10 compression, R20 rebound. Spring rate: S size 411 lbs, size M 457 lbs, ML size 502 lbs, L size 548 lbs, XL size 605 lbs
<b>FORK</b>	Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm, Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Acros custom ZS56/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock
<b>STEM</b>	Onoff S9 30mm 0°, Full CNC, 31,8mm barbore
<b>HANDLEBAR</b>	Onoff S6 1,0 Carbon, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31,8mm barbore, L and XL size: 1.5 rise
<b>GRIPS</b>	Onoff Desert Pro, CNC lock-on, 135mm, L and XL: Thicker size
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31,6mm, IX Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), ML size: 180-155mm (468-275mm), L size: 210-185mm (528-305mm), XL size: 210-185mm (528-305mm)
<b>SADDLE</b>	Ergon SM-10
<b>FRONT BRAKE</b>	Sram Maven Silver, 18 and 19.5-millimeter 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>REAR BRAKE</b>	Sram Maven Silver, 18 and 19.5-millimeter 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>BRAKE LEVER</b>	Sram Maven Silver, SwingLink and lever pivot bushings, tools-free reach adjust
<b>RIMS</b>	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFP, tubeless, 28 spokes
<b>SPOKES</b>	Mavic straight-pull double butted, contactless lacing

<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts
<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub
<b>FRONT TIRE</b>	Maxxis Assegai 29x2.6WT, tubeless ready, 3C MAXX GRIP compound, DD protection, 60x2TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6 WT, tubeless ready, 3C MaxxTerra compound, DD protection, 2x120TPI, folding bead
<b>CRANKSET</b>	E.13 Helix Race Carbon E*Spec Plus, All sizes: 160mm
<b>RINGS</b>	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Sram GX Eagle T-Type, 12s, Powerlock
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Sram X0 Eagle AXS, T-Type, 12s
<b>SHIFT LEVERS</b>	Sram Eagle AXS Pod MMX, 12s
<b>CASSETTE</b>	Sram XS-1295, 10-52T, T-Type, 12s
<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BATTERY</b>	Bosch Powertube 600Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	--
<b>OTHERS</b>	--
<b>WEIGHT</b>	--





## CRAFTY CARBON RR S

Black / Bunker Grey / Carrera Blue



**FRAME** STEALTH AIR FULL CARBON • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT600Wh, 250Wh POWERMORE OPTIONAL • **FORK** FOX 38 GRIP X2 FACTORY, 160mm • **REAR SHOCK** FOX FLOAT X FACTORY EVOL • **SEATPOST** FOX TRANSFER FACTORY ADJUSTABLE TRAVEL • **BRAKES** SRAM MAVEN SILVER • **WHEELS** MAVIC E-DEEMAX S • **REAR DERAILLEUR** SRAM XO EAGLE AXS T-TYPE



## e-MTB ENDURO / CRAFTY CARBON RR S

Black / Bunker Grey / Carrera Blue

<b>FRAME</b>	Crafty Stealth Air full Carbon, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm
<b>REAR SHOCK</b>	Fox Float-X Factory Kashima EVOL LV, 185x55mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	CS40 compression, RL60 rebound, Rezi B40, LML, 0.2 volume spacer
<b>FORK</b>	Fox 38 29 Float GRIPX2 Factory Kashima, 160mm, tapered steerer tube, Boost 15x110mm Kabolt axle, 44mm offset, Settings: high and low-speed compression, high and low-speed rebound, air preload
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Acros custom ZS56/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm barbore
<b>HANDLEBAR</b>	Onoff S6 1.0 Carbon, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore, L and XL size: 1.5 rise
<b>GRIPS</b>	Onoff Desert Pro, CNC lock-on, 135mm, L and XL: Thicker size
<b>SEATPOST</b>	Fox Transfer Factory Kashima internal, adjustable travel, diameter 31.6mm, S size: 95mm -120mm, M size: 125mm -150mm, ML size L size: 155mm -180mm, L size: 155mm -180mm, XL size: 185mm -210mm
<b>SADDLE</b>	Ergon SM-10
<b>FRONT BRAKE</b>	Sram Maven Silver, 18 and 19.5-millimeter 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>REAR BRAKE</b>	Sram Maven Silver, 18 and 19.5-millimeter 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>BRAKE LEVER</b>	Sram Maven Silver, SwingLink and lever pivot bushings, tools-free reach adjust
<b>RIMS</b>	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFP, tubeless, 28 spokes
<b>SPOKES</b>	Mavic straight-pull double butted, contactless lacing

<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts
<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub
<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect-R ebike, 160mm
<b>RINGS</b>	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Sram GX Eagle T-Type, 12s, Powerlock
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Sram X0 Eagle AXS, T-Type, 12s
<b>SHIFT LEVERS</b>	Sram Eagle AXS Pod MMX, 12s
<b>CASSETTE</b>	Sram XS-1295, 10-52T, T-Type, 12s
<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BATTERY</b>	Bosch Powertube 600Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	--
<b>OTHERS</b>	--
<b>WEIGHT</b>	--



## CRAFTY CARBON RR

Earth Red / Black / Flame Red



**FRAME** STEALTH AIR CARBON + STEALTH ALLOY REAR TRIANGLE • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT800Wh, 250Wh POWERMORE OPTIONAL • **FORK** FOX 38 GRIP X2 FACTORY, 160mm • **REAR SHOCK** FOX FLOAT X FACTORY EVOL  
• **SEATPOST** ONOFF PIJA ADJUSTABLE LENGTH • **BRAKES** SRAM MAVEN BRONZE • **WHEELS** MAVIC E-DEEMAX  
• **REAR DERAILLEUR** SRAM GX EAGLE AXS T-TYPE



## e-MTB ENDURO / CRAFTY CARBON RR

Earth Red / Black / Flame Red

<b>FRAME</b>	Crafty Stealth Air full Carbon front triangle, Stealth Alloy rear triangle, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm
<b>REAR SHOCK</b>	Fox Float X Factory Kashima EVOL, 185x55mm. Settings: 2-position compression (Open/Firm), rebound, air preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	CS40 compression, RL60 rebound, Rezi B40, LML, 0.2 volume spacer
<b>FORK</b>	Fox 38 29 Float GRIPX2 Factory Kashima, 160mm, tapered steerer tube, Boost 15x110mm Kabolt axle, 44mm offset. Settings: high and low-speed compression, high and low-speed rebound, air preload
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Acros custom ZS56/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff S6 1.0 7050 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise
<b>GRIPS</b>	Onoff Forest, CNC lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), ML size: 180-155mm (468-275mm), L size: 210-185mm (528-305mm), XL size: 210-185mm (528-305mm)
<b>SADDLE</b>	Ergon SM-10
<b>FRONT BRAKE</b>	Sram Maven Bronze, 18 and 19.5-millimeter 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>REAR BRAKE</b>	Sram Maven Bronze, 18 and 19.5-millimeter 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>BRAKE LEVER</b>	Sram Maven Bronze, SwingLink and lever pivot bushings, tools-free reach adjust
<b>RIMS</b>	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
<b>SPOKES</b>	Mavic J-bend double butted, contactless lacing
<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts

<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub
<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect-R ebike, 160mm
<b>RINGS</b>	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Sram GX Eagle T-Type, 12s, Powerlock
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Sram GX Eagle AXS, T-Type, 12s
<b>SHIFT LEVERS</b>	Sram Eagle AXS Pod MMX, 12s
<b>CASSETTE</b>	Sram XS-1275, 10-52T, T-Type, 12s
<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Kw/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BATTERY</b>	Bosch Powertube 800Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	--
<b>OTHERS</b>	--
<b>WEIGHT</b>	--



## CRAFTY CARBON R

Black / Nimbus Grey / Tonic Gold



**FRAME** STEALTH AIR CARBON + STEALTH ALLOY REAR TRIANGLE • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT800Wh, 250Wh POWERMORE OPTIONAL • **FORK** FOX 38 GRIP PERFORMANCE, 160mm • **REAR SHOCK** FOX FLOAT X PERFORMANCE  
• **SEATPOST** ONOFF PIJA ADJUSTABLE LENGTH • **BRAKES** SHIMANO XT M8120 • **WHEELS** MAVIC E-DEEMAX  
• **REAR DERAILLEUR** SHIMANO XT M8100



## e-MTB ENDURO / CRAFTY CARBON R

Black / Nimbus Grey / Tonic Gold

<b>FRAME</b>	Crafty Stealth Air full Carbon front triangle, Stealth Alloy rear triangle, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm
<b>REAR SHOCK</b>	Fox Float-X LV Performance, 185x55mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	C540 compression, RL60 rebound, Rezi B40, LML, 0.2 volume spacer
<b>FORK</b>	Fox 38 29 Float GRIP Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Acros custom Z556/Z556, 1-1/8", 1.5" head tube, internal cable routing, sealing plugs without blocklock
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff S6 1.0 7050 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise
<b>GRIPS</b>	Onoff Forest, CNC lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, IX Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), ML size: 180-155mm (468-275mm), L size: 210-185mm (528-305mm), XL size: 210-185mm (528-305mm)
<b>SADDLE</b>	Ergon SM-10
<b>FRONT BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>REAR BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>BRAKE LEVER</b>	Shimano XT M8100, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust
<b>RIMS</b>	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
<b>SPOKES</b>	Mavic J-bend double butted, contactless lacing
<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts

<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, MS freehub
<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect-R ebike, 160mm
<b>RINGS</b>	Race Face, 34T, steel, direct mount
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Shimano XT M8100, 12s
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Shimano XT M8100, SGS, Shadow+
<b>SHIFT LEVERS</b>	Shimano XT M8100, Rapid Fire Plus, 12s
<b>CASSETTE</b>	Shimano XT M8100 10-51T Hyperglide+, 12s
<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Kw/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BATTERY</b>	Bosch Powertube 800Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	Sram UDH
<b>OTHERS</b>	--
<b>WEIGHT</b>	--





## CRAFTY CARBON R

Bunker Grey / Fog Grey / Flame Red



**FRAME** STEALTH AIR CARBON + STEALTH ALLOY REAR TRIANGLE • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT800Wh, 250Wh POWERMORE OPTIONAL • **FORK** FOX 38 GRIP PERFORMANCE, 160mm • **REAR SHOCK** FOX FLOAT X PERFORMANCE  
• **SEATPOST** ONOFF PIJA ADJUSTABLE LENGTH • **BRAKES** SHIMANO XT M8120 • **WHEELS** MAVIC E-DEEMAX  
• **REAR DERAILLEUR** SHIMANO XT M8100



## e-MTB ENDURO / CRAFTY CARBON R

Bunker Grey / Fog Grey / Flame Red

<b>FRAME</b>	Crafty Stealth Air full Carbon front triangle, Stealth Alloy rear triangle, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm
<b>REAR SHOCK</b>	Fox Float-X LV Performance, 185x55mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	C540 compression, RL60 rebound, Rezi B40, LML, 0.2 volume spacer
<b>FORK</b>	Fox 38 29 Float GRIP Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Acros custom Z556/Z556, 1-1/8", 1.5" head tube, internal cable routing, sealing plugs without blocklock
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff S6 1.0 7050 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise
<b>GRIPS</b>	Onoff Forest, CNC lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, IX Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), ML size: 180-155mm (468-275mm), L size: 210-185mm (528-305mm), XL size: 210-185mm (528-305mm)
<b>SADDLE</b>	Ergon SM-10
<b>FRONT BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>REAR BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>BRAKE LEVER</b>	Shimano XT M8100, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust
<b>RIMS</b>	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
<b>SPOKES</b>	Mavic J-bend double butted, contactless lacing
<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts

<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, MS freehub
<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect-R ebike, 160mm
<b>RINGS</b>	Race Face, 34T, steel, direct mount
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Shimano XT M8100, 12s
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Shimano XT M8100, SGS, Shadow+
<b>SHIFT LEVERS</b>	Shimano XT M8100, Rapid Fire Plus, 12s
<b>CASSETTE</b>	Shimano XT M8100 10-51T Hyperglide+, 12s
<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Kw/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BATTERY</b>	Bosch Powertube 800Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	Sram UDH
<b>OTHERS</b>	--
<b>WEIGHT</b>	--



## CRAFTY RACE

Obsidian Grey / Dense Yellow / Racing Silver



**FRAME** STEALTH ALLOY • **MOTOR** BOSCH PERFORMANCE LINE CX-RACE (25KM/H) SMART SYSTEM • **FORK** FOX 38 GRIP PERFORMANCE, 160mm • **REAR SHOCK** FOX FLOAT X PERFORMANCE • **WHEELS** MAVIC E-DEEMAX • **BRAKES** SHIMANO XT M8120  
• **CRANKSET** RACE FACE AEFFECT, 160mm • **REAR DERAILLEUR** SHIMANO XT M8100



## e-MTB ENDURO / CRAFTY RACE

Obsidian Grey / Dense Yellow / Racing Silver

<b>FRAME</b>	Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
<b>REAR SHOCK</b>	Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
<b>SHOCK SETTINGS</b>	medium compression, medium rebound, air volume spacer 0.2
<b>FORK</b>	Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
<b>STEM</b>	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
<b>GRIPS</b>	Onoff Desert, 1lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm
<b>SADDLE</b>	Ergon SM-10
<b>FRONT BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>REAR BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>BRAKE LEVER</b>	Shimano XT M8100, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust
<b>RIMS</b>	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
<b>SPOKES</b>	Mavic J-bend double butted, contactless lacing
<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts
<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, MS freehub

<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect-R ebike, 160mm
<b>RINGS</b>	Race Face, 34T, steel, direct mount
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Shimano XT M8100, 12s
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Shimano XT M8100, SGS, Shadow+
<b>SHIFT LEVERS</b>	Shimano XT M8100, Rapid Fire Plus, 12s
<b>CASSETTE</b>	Shimano XT M8100 10-51T Hyperglide+, 12s
<b>MOTOR</b>	Bosch Performance Line CX-Race (25Km/h) GEN4 SMART SYSTEM
<b>BATTERY</b>	Bosch Powertube 750Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	Mondraker M068
<b>OTHERS</b>	--
<b>WEIGHT</b>	--