

S-WORKS TURBO LEVO SL 2

EUR 14.000,00



Brown Tint / Gunmetal Impasto / Ashen Grey / Brushed Liquid Metal



Powdered Indigo Tint / Cool Grey Impasto / Midnight Shadow / Bronze

Das S-Works Turbo Levo SL zeichnet sich durch exzellente Fahrqualitäten, vielseitige Einsatzgebiete und einen flüsterleisen Motor aus. Wenn du dich nach serpentinendurchsetzten Singletrails sehnst, dir kein Sprung zu hoch oder zu weit ist und du dafür lebst, deine Skills und Fitness zu verbessern, dann ist das neue Levo SL genau das Richtige für dich. Die Verschmelzung der einzigartigen Trailbike-Performance mit der natürlichen Motorunterstützung wird dich umhauen. Diese Power gibt dir die Möglichkeit, mehr Trails zu fahren als jemals zuvor. Vergleiche es mit anderen Trailbikes, ob mit oder ohne Motor, und du wirst sehen: Das Levo SL ist das ultimative Trailbike.

S-WORKS TURBO LEVO SL 2	S2	S3	S4	S5	S6
Stack (mm)	617	626	635	645	654
Reach (mm)	425	445	470	495	525
Head-Tube Length (mm)	100	110	120	130	140
Head-Tube Angle (deg)	64.6	64.6	64.6	64.6	64.6
B-B Height (mm)	348	348	348	348	348
B-B Drop (mm)	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132
Fork Length, Full (mm)	570	570	570	570	570
Fork Rake/Offset (mm)	42	42	42	42	42
Front-Center (mm)	752	776	806	835	869
Chainstay Length (mm)	432	432	432	432	432
Wheelbase (mm)	1184	1208	1238	1267	1301
Top Tube Length, Horizontal (mm)	582	604	631	659	691
Bike Standover Height (mm)	763	766	767	773	778
Seat-Tube Length (mm)	385	405	425	445	465
Seat-Tube Angle (deg)	75.8	75.8	75.8	75.8	75.8
Crank Length (mm)	165	170	170	170	175
Handlebar Width (mm)	780	780	780	780	780
Stem Length (mm)	35	35	35	50	50
Saddle Width (mm)	155	143	143	143	143
Seatpost Length (mm)	125	150	170	170	170

SPECS	Technische Änderungen vorbehalten.
Rahmen	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Dämpfer	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Gabel	Fox 36 Factory series, 29", Grip X2 damper, Kashima, S1: 150mm, S2-S6: 160mm
Vorbau	Industry 9 A35 stem, 40mm length, 35mm clamp diameter
Griffe	Deity Lockjaw grips
Lenker	Raceface Era Carbon, S3-S6: 40mm rise, S1/S2: 20mm rise
Bremse Vorne	SRAM Maven Ultimate w/Hs2 rotor, 200mm
Bremse Hinten	SRAM Maven Ultimate w/Hs2 rotor, 200mm
Schaltwerk	SRAM XX Eagle Transmission Derailleur
Schalthebel	SRAM AXS POD Ultimate Controller
Kassette	SRAM XX Eagle Transmission Cassette, 12spd, 10-52t
Kurbelgarnitur	SRAM Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Kette	SRAM XX Eagle Transmission Flattop Chain
Kettenblatt	SRAM T-type ring, 32t
Vorderrad	Traverse HD 240, 29"
Hinterrad	Traverse HD 240, 27.5", XD freehub body
Vorderreifen	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Hinterreifen	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Schläuche	Presta, Standard Valve
Sattelstütze	RockShox Reverb AXS, 30.9, 1X remote, (S1:100mm, S2: 125mm, S3: 150mm, S4-S6: 170mm)
Sattelstützklemme	Alloy, 38.6mm
Sattel	Specialized Power Pro Mirror, hollow Ti rail
Motor	Specialized 1.2 SL Custom Rx Trail Tuned Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Akku	Specialized SL1-320, fully integrated, 320Wh
Ladegerät	Custom charger, 48V System w/ SL system charger plug
Kabelbaum	Custom Specialized wiring harness
Gewicht	18.15 kg (Größe: S4)

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
96825-0102	Levo SL SW Carbon	Brown Tint / Gunmetal Impasto / Ashen Grey / Brushed Liquid Metal	S2
96825-0103			S3
96825-0104			S4
96825-0105			S5
96825-0106			S6
96825-0202		Powdered Indigo Tint / Cool Grey Impasto / Midnight Shadow / Bronze	S2
96825-0203			S3
96825-0204			S4
96825-0205			S5
96825-0206			S6

S-WORKS TURBO LEVO SL 2 FRAMESET

EUR 7.000,00



Team Yellow Tint / Pearl Impasto / Dark Moss Green / Metallic White Silver

Das S-Works Turbo Levo SL zeichnet sich durch exzellente Fahrqualitäten, vielseitige Einsatzgebiete und einen flüsterleisen Motor aus. Wenn du dich nach serpentinendurchsetzten Singletrails sehnst, dir kein Sprung zu hoch oder zu weit ist und du dafür lebst, deine Skills und Fitness zu verbessern, dann ist das neue Levo SL genau das Richtige für dich. Die Verschmelzung der einzigartigen Trailbike-Performance mit der natürlichen Motorunterstützung wird dich umhauen. Diese Power gibt dir die Möglichkeit, mehr Trails zu fahren als jemals zuvor. Vergleiche es mit anderen Trailbikes, ob mit oder ohne Motor, und du wirst sehen: Das Levo SL ist das ultimative Trailbike.

S-WORKS TURBO LEVO SL 2	S2	S3	S4	S5	S6
Stack (mm)	617	626	635	645	654
Reach (mm)	425	445	470	495	525
Head-Tube Length (mm)	100	110	120	130	140
Head-Tube Angle (deg)	64.6	64.6	64.6	64.6	64.6
B-B Height (mm)	348	348	348	348	348
B-B Drop (mm)	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132
Fork Length, Full (mm)	570	570	570	570	570
Fork Rake/Offset (mm)	42	42	42	42	42
Front-Center (mm)	752	776	806	835	869
Chainstay Length (mm)	432	432	432	432	432
Wheelbase (mm)	1184	1208	1238	1267	1301
Top Tube Length, Horizontal (mm)	582	604	631	659	691
Bike Standover Height (mm)	763	766	767	773	778
Seat-Tube Length (mm)	385	405	425	445	465
Seat-Tube Angle (deg)	75.8	75.8	75.8	75.8	75.8
Crank Length (mm)	165	170	170	170	175
Handlebar Wigth (mm)	780	780	780	780	780
Stem Length (mm)	35	35	35	50	50
Saddle Width (mm)	155	143	143	143	143
Seatpost Length (mm)	125	150	170	170	170

SPECS	Technische Änderungen vorbehalten.
Rahmen	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Dämpfer	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Kurbelgarnitur	SRAM Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Kettenblatt	SRAM T-type ring, 32t
Sattelstützklemme	Alloy, 38.6mm
Motor	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Ul/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Akku	Specialized SL1-320, fully integrated, 320Wh
Ladegerät	Custom charger, 48V System w/ SL system charger plug
Kabelbaum	Custom Specialized wiring harness
Gewicht	5.86 kg (Größe: S4)

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
76825-0002	Levo SL SW Carbon Frm	Team Yellow Tint / Pearl Impasto / Dark Moss Green / Metallic White Silver	S2
76825-0003			S3
76825-0004			S4
76825-0005			S5
76825-0006			S6

TURBO LEVO SL PRO CARBON

EUR 11.500,00



Orange Tint / Cool Grey Impasto / Copper

Das Turbo Levo SL zeichnet sich durch exzellente Fahrqualitäten, ein vielseitiges Einsatzgebiet und flüsterleiser Verstärkung deiner Leistungsfähigkeit aus. Wenn du dich nach serpentinendurchsetzten Singletrails sehnst, dir kein Sprung zu hoch oder zu weit ist und du dafür lebst, deine Skills und Fitness zu verbessern, dann ist das neue Levo SL genau das Richtige für dich. Die Verschmelzung der einzigartigen Trailbike-Performance mit der natürlichen Motorunterstützung wird dich umhauen. Diese Power gibt dir die Möglichkeit, mehr Trails zu fahren als jemals zuvor. Vergleiche es mit jedem anderen Trailbike, ob mit oder ohne Motor, und du wirst sehen: Das Levo SL ist das ultimative Trailbike.

TURBO LEVO SL	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Head-Tube Length (mm)	95	100	110	120	130	140
Head-Tube Angle (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
B-B Height (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Fork Length, Full (mm)	560	570	570	570	570	570
Fork Rake/Offset (mm)	42	42	42	42	42	42
Front-Center (mm)	726	752	776	806	835	869
Chainstay Length (mm)	433	432	432	432	432	432
Wheelbase (mm)	1158	1184	1208	1238	1267	1301
Bike Stand-Over Height (mm)	727	763	766	767	773	778
Seat-Tube Length (mm)	385	385	405	425	445	465
Seat-Tube Angle (mm)	75.8	75.8	75.8	75.8	75.8	75.8
Kurbellänge (mm)	165	165	170	170	170	175
Lenkerbreite (mm)	780	780	780	780	780	780
Vorbaulänge (mm)	35	35	35	35	50	50
Sattelbreite (mm)	155	155	143	143	143	143
Länge Sattelstütze (mm)	100	125	150	170	170	170

SPECS

Technische Änderungen vorbehalten.

Rahmen	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Dämpfer	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Gabel	Fox 36 Factory series, 29", Grip X2 damper, Kashima, S1: 150mm, S2-S6: 160mm
Vorbau	Industry 9 A35 stem, 40mm length, 35mm clamp diameter
Griffe	Deity Lockjaw grips
Lenker	RaceFace Era Carbon, riser bar, 5-degree upsweep, 8-degree backsweep, S2:20mm Rise, S3-S6:40mm Rise, 800mm
Bremse Vorne	SRAM Maven Silver w/Hs2 rotor, 200mm
Bremse Hinten	SRAM Maven Silver w/Hs2 rotor, 200mm
Schaltwerk	SRAM X0 Eagle Transmission Derailleur
Schalthebel	SRAM AXS POD Controller
Kassette	SRAM X0 Eagle Transmission Cassette, 12spd, 10-52t
Kurbelgarnitur	SRAM Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Kettenblätter	SRAM T-type ring, 32t
Kette	SRAM X0 Eagle Transmission Flattop Chain
Vorderrad	Traverse HD 350, 29"
Hinterrad	Traverse HD 350, 27.5", XD freehub body
Vorderreifen	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Hinterreifen	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Schläuche	Standard, Presta Valve
Sattelstütze	Bike Yoke, Revive Max, 34.9, S1: 125mm, S2: 160mm, S3-S4: 185mm, S5-S6: 213mm
Sattelstützklemme	Alloy, 38.6mm
Sattel	Specialized Bridge Expert Mimic, hollow ti rail
Motor	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Display	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Akku	Specialized SL1-320, fully integrated, 320Wh
Ladegerät	Custom charger, 48V System w/ SL system charger plug
Kabelbaum	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Gewicht	18.15 kg (Größe: S4)

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
96825-1001	Levo SL Pro Carbon	Orange Tint / Cool Grey Impasto / Copper	S1
96825-1002			S2
96825-1003			S3
96825-1004			S4
96825-1005			S5
96825-1006			S6

TURBO LEVO SL ÖHLINS COIL

EUR 9.900,00



Solidity / Maroon / Burnt Gold Metallic

Das Turbo Levo SL zeichnet sich durch exzellente Fahrqualitäten, ein vielseitiges Einsatzgebiet und flüsterleiser Verstärkung deiner Leistungsfähigkeit aus. Wenn du dich nach serpentinendurchsetzten Singletrails sehnst, dir kein Sprung zu hoch oder zu weit ist und du dafür lebst, deine Skills und Fitness zu verbessern, dann ist das neue Levo SL genau das Richtige für dich. Die Verschmelzung der einzigartigen Trailbike-Performance mit der natürlichen Motorunterstützung wird dich umhauen. Diese Power gibt dir die Möglichkeit, mehr Trails zu fahren als jemals zuvor. Vergleiche es mit jedem anderen Trailbike, ob mit oder ohne Motor, und du wirst sehen: Das Levo SL ist das ultimative Trailbike.

TURBO LEVO SL	S2	S3	S4	S5	S6
Stack (mm)	617	626	635	645	654
Reach (mm)	425	445	470	495	525
Head-Tube Length (mm)	100	110	120	130	140
Head-Tube Angle (degrees)	64.6	64.6	64.6	64.6	64.6
B-B Height (mm)	348	348	348	348	348
B-B Drop (mm)	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132
Fork Length, Full (mm)	570	570	570	570	570
Fork Rake/Offset (mm)	42	42	42	42	42
Front-Center (mm)	752	776	806	835	869
Chainstay Length (mm)	432	432	432	432	432
Wheelbase (mm)	1184	1208	1238	1267	1301
Bike Stand-Over Height (mm)	763	766	767	773	778
Seat-Tube Length (mm)	385	405	425	445	465
Seat-Tube Angle (mm)	75.8	75.8	75.8	75.8	75.8
Kurbellänge (mm)	165	170	170	170	175
Lenkerbreite (mm)	780	780	780	780	780
Vorbaulänge (mm)	35	35	35	50	50
Sattelpfostenbreite (mm)	155	143	143	143	143
Länge Sattelstütze (mm)	125	150	170	170	170

SPECS	Technische Änderungen vorbehalten.
Rahmen	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Dämpfer	Ohlins TTX Coil shock, S2: 411lb, S3: 457lb, S4: 502lb, S5: 548lb, S6: 605lb
Gabel	Ohlins RXF 38, 160mm travel, 29"
Vorbau	RaceFace Aeffect R 35mm bore, 40mm length
Griffe	Deity Grips
Lenker	Raceface Turbine Alloy, 35mm dia, S1/S2: 20mm rise, 800mm width, S3-S6: 40mm rise, 800mm width
Bremse Vorne	Tektro DHR Evo brakes, w/220mm rotor
Bremse Hinten	Tektro DHR Evo brakes, w/220mm rotor
Schaltwerk	SRAM GX Eagle Transmission Derailleur
Schalthebel	SRAM AXS POD Controller
Kassette	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
Kurbelgarnitur	SRAM GX Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Kettenblätter	SRAM T-type ring, 32t
Kette	SRAM GX Eagle Transmission Flattop Chain
Vorderrad	Roval Traverse Alloy 29"
Hinterrad	Roval Traverse Alloy 27.5", XD freehub body
Vorderreifen	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Hinterreifen	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 27.5x2.3"
Schläuche	Standard, Presta Valve
Sattelstütze	Bike Yoke, Revive Max, 34.9, S1: 125mm, S2: 160mm, S3-S4: 185mm, S5-S6: 213mm
Sattelstützklammer	Alloy, 38.6mm
Sattel	Specialized Bridge Mimic, hollow chromo rail
Motor	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Display	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Akku	Specialized SL1-320, fully integrated, 320Wh
Ladegerät	Custom charger, 48V System w/ SL system charger plug
Kabelbaum	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Gewicht	19.61 kg (Größe: S4)

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
96825-0002	Levo SL Öhlins Coil	Solidity / Maroon / Burnt Gold Metallic	S2
96825-0003			S3
96825-0004			S4
96825-0005			S5
96825-0006			S6

TURBO LEVO SL EXPERT CARBON

EUR 9.600,00



Carbon / Obsidian / Bronze



Champaign / Cool Grey / Metallic Obsidian

Das Turbo Levo SL zeichnet sich durch exzellente Fahrqualitäten, ein vielseitiges Einsatzgebiet und flüsterleiser Verstärkung deiner Leistungsfähigkeit aus. Wenn du dich nach serpentinendurchsetzten Singletrails sehnst, dir kein Sprung zu hoch oder zu weit ist und du dafür lebst, deine Skills und Fitness zu verbessern, dann ist das neue Levo SL genau das Richtige für dich. Die Verschmelzung der einzigartigen Trailbike-Performance mit der natürlichen Motorunterstützung wird dich umhauen. Diese Power gibt dir die Möglichkeit, mehr Trails zu fahren als jemals zuvor. Vergleiche es mit jedem anderen Trailbike, ob mit oder ohne Motor, und du wirst sehen: Das Levo SL ist das ultimative Trailbike.

TURBO LEVO SL	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Head-Tube Length (mm)	95	100	110	120	130	140
Head-Tube Angle (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
B-B Height (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Fork Length, Full (mm)	560	570	570	570	570	570
Fork Rake/Offset (mm)	42	42	42	42	42	42
Front-Center (mm)	726	752	776	806	835	869
Chainstay Length (mm)	433	432	432	432	432	432
Wheelbase (mm)	1158	1184	1208	1238	1267	1301
Bike Stand-Over Height (mm)	727	763	766	767	773	778
Seat-Tube Length (mm)	385	385	405	425	445	465
Seat-Tube Angle (mm)	75.8	75.8	75.8	75.8	75.8	75.8
Kurbellänge (mm)	165	165	170	170	170	175
Lenkerbreite (mm)	780	780	780	780	780	780
Vorbaulänge (mm)	35	35	35	35	50	50
Sattelbreite (mm)	155	155	143	143	143	143
Länge Sattelstütze (mm)	100	125	150	170	170	170

SPECS

SPECS	Technische Änderungen vorbehalten.
Rahmen	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Dämpfer	FOX FLOAT Performance Elite with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Gabel	Fox 36 Performance Elite series, 29", Grip X2 damper, S1: 150mm, S2-S6: 160mm
Vorbau	Alloy Trail Stem, 35mm bar bore
Griffe	Specialized Trail Grips
Lenker	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise: S3-S4: 800 width, 30mm rise: S5-S6: 800 width, 40mm rise
Bremse Vorne	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm
Bremse Hinten	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm
Schaltwerk	SRAM GX Eagle Transmission Derailleur
Schalthebel	SRAM AXS POD Controller
Kassette	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
Kurbelgarnitur	SRAM GX Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Kettenblätter	SRAM T-type ring, 32t
Kette	SRAM GX Eagle Transmission Flattop Chain
Vorderrad	Roval Traverse Alloy 29"
Hinterrad	Roval Traverse Alloy 27.5", XD freehub body
Vorderreifen	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Hinterreifen	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Schläuche	Standard, Presta Valve
Sattelstütze	PNW Loam post w/travel adjust S1: 125mm, S2: 150mm, S3: 170mm, S4/S5/S6: 200mm
Sattelstützklemme	Alloy, 38.6mm
Sattel	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Motor	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Display	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Akku	Specialized SL1-320, fully integrated, 320Wh
Ladegerät	Custom charger, 48V System w/ SL system charger plug
Kabelbaum	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Gewicht	18.98 kg (Größe: S4)

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
96825-3001	Levo SL Expert Carbon	Carbon / Obsidian / Bronze	S1
96825-3002			S2
96825-3003			S3
96825-3004			S4
96825-3005			S5
96825-3006			S6
96825-3101		Champaign / Cool Grey / Metallic Obsidian	S1
96825-3102			S2
96825-3103			S3
96825-3104			S4
96825-3105			S5
96825-3106			S6

TURBO LEVO SL COMP CARBON

EUR 7.900,00



Cypress Metallic / Cypress / Dark Moss Green



Spice / Maroon / Obsidian

Das Turbo Levo SL zeichnet sich durch exzellente Fahrqualitäten, ein vielseitiges Einsatzgebiet und flüsterleiser Verstärkung deiner Leistungsfähigkeit aus. Wenn du dich nach serpentinendurchsetzten Singletrails sehnst, dir kein Sprung zu hoch oder zu weit ist und du dafür lebst, deine Skills und Fitness zu verbessern, dann ist das neue Levo SL genau das Richtige für dich. Die Verschmelzung der einzigartigen Trailbike-Performance mit der natürlichen Motorunterstützung wird dich umhauen. Diese Power gibt dir die Möglichkeit, mehr Trails zu fahren als jemals zuvor. Vergleiche es mit jedem anderen Trailbike, ob mit oder ohne Motor, und du wirst sehen: Das Levo SL ist das ultimative Trailbike.

TURBO LEVO SL	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Head-Tube Length (mm)	95	100	110	120	130	140
Head-Tube Angle [degrees]	64.6	64.6	64.6	64.6	64.6	64.6
B-B Height (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Fork Length, Full (mm)	560	570	570	570	570	570
Fork Rake/Offset (mm)	42	42	42	42	42	42
Front-Center (mm)	726	752	776	806	835	869
Chainstay Length (mm)	433	432	432	432	432	432
Wheelbase (mm)	1158	1184	1208	1238	1267	1301
Bike Stand-Over Height (mm)	727	763	766	767	773	778
Seat-Tube Length (mm)	385	385	405	425	445	465
Seat-Tube Angle (mm)	75.8	75.8	75.8	75.8	75.8	75.8
Kurbellänge (mm)	165	165	170	170	170	175
Lenkerbreite (mm)	780	780	780	780	780	780
Vorbaulänge (mm)	35	35	35	35	50	50
Sattelbreite (mm)	155	155	143	143	143	143
Länge Sattelstütze (mm)	100	125	150	170	170	170

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
96825-5201	Levo SL Comp Carbon	Cypress Metallic / Cypress / Dark Moss Green	S1
96825-5202			S2
96825-5203			S3
96825-5204			S4
96825-5205			S5
96825-5206			S6
96825-5301		Spice / Maroon / Obsidian	S1
96825-5302			S2
96825-5303			S3
96825-5304			S4
96825-5305			S5
96825-5306			S6

SPECS

SPECS	Technische Änderungen vorbehalten.
Rahmen	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Dämpfer	FOX FLOAT Performance with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/ LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Gabel	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, S1:150mm of travel, S2-S6:160mm of travel
Vorbau	Alloy Trail Stem, 35mm bar bore
Griffe	Specialized Trail Grips
Lenker	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise: S3-S4: 800 width, 30mm rise: S5-S6: 800 width, 40mm rise
Bremse Vorne	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm Centerline rotor
Bremse Hinten	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm Centerline rotor
Schaltwerk	SRAM S1000 Eagle Transmission Derailleur
Schalthebel	SRAM AXS POD Controller
Kassette	SRAM XS-1270 Transmission Cassette, 12spd, 10-52t
Kurbelgarnitur	SRAM S1000 Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Kettenblätter	SRAM T-type ring, 32t
Kette	SRAM GX Eagle Transmission Flattop Chain
Felgen	Specialized 29/27.5, hookless alloy, 30mm inner width, tubeless ready
Vorderradnabe	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Hinterradnabe	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Speichen	DT Swiss Industry
Vorderreifen	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Hinterreifen	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Schläuche	Standard, Presta Valve
Sattelstütze	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4: 170mm, S5/S6: 190mm
Sattelstützklemme	Alloy, 38.6mm
Sattel	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Motor	Specialized SL1-320, fully integrated, 320Wh
Display	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Akku	Specialized SL1-320, fully integrated, 320Wh
Ladegerät	Custom charger, 48V System w/ SL system charger plug
Kabelbaum	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Gewicht	19.11 kg [Größe: S4]

TURBO LEVO SL COMP ALLOY

EUR 6.600,00



Cool Grey / Ashen Grey / Dune White



Cast Blue Metallic / Dark Navy / White Mountains

Das Turbo Levo SL Comp Alloy zeichnet sich durch exzellente Fahrqualitäten, vielseitige Einsatzgebiete und einen flüsterleisen Motor aus. Wenn du dich nach serpentinendurchsetzten Singletrails sehnst, dir kein Sprung zu hoch oder zu weit ist und du dafür lebst, deine Skills und Fitness zu verbessern, dann ist das neue Levo SL Alloy genau das Richtige für dich. Die Verschmelzung der einzigartigen Trailbike-Performance mit der natürlichen Motorunterstützung wird dich umhauen. Diese Power gibt dir die Möglichkeit, mehr Trails zu fahren als jemals zuvor. Vergleiche es mit anderen Trailbikes, ob mit oder ohne Motor, und du wirst sehen: Das Levo SL Alloy ist das ultimative Trailbike.

TURBO LEVO SL	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Head-Tube Length (mm)	95	100	110	120	130	140
Head-Tube Angle (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
B-B Height (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Fork Length, Full (mm)	560	570	570	570	570	570
Fork Rake/Offset (mm)	42	42	42	42	42	42
Front-Center (mm)	726	752	776	806	835	869
Chainstay Length (mm)	433	432	432	432	432	432
Wheelbase (mm)	1158	1184	1208	1238	1267	1301
Top Tube Length, Horizontal (mm)	560	582	604	631	659	691
Bike Stand-Over Height (mm)	727	763	766	767	773	778
Seat-Tube Length (mm)	385	385	405	425	445	465
Seat-Tube Angle (mm)	75.8	75.8	75.8	75.8	75.8	75.8

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
96825-5001	Levo SL Comp Alloy	Cast Blue Metallic / Dark Navy / White Mountains	S1
96825-5002			S2
96825-5003			S3
96825-5004			S4
96825-5005			S5
96825-5006			S6
96825-5101		Cool Grey / Ashen Grey / Dune White	S1
96825-5102			S2
96825-5103			S3
96825-5104			S4
96825-5105			S5
96825-5106			S6

SPECS	Technische Änderungen vorbehalten.
Rahmen	Levo SL Alloy Frame, M5 alloy, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels
Dämpfer	FOX FLOAT Performance with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/ LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Gabel	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
Vorbau	Alloy Trail Stem, 35mm bar bore
Griffe	Specialized Trail Grips
Lenker	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise: S3-S4: 800 width, 30mm rise: S5-S6: 800 width, 40mm rise
Bremse Vorne	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm Centerline rotor
Bremse Hinten	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm Centerline rotor
Schaltwerk	Sram X01 Eagle, 12-speed
Schalthebel	SRAM GX Eagle, trigger, 12-speed, single click
Kassette	Sram XG-1275, 12-speed, 10-52t
Kurbelgarnitur	SRAM S1000 Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Kette	SRAM GX Eagle, 12-speed
Kettenblatt	SRAM T-type ring, 32t
Felgen	Specialized 29/27.5, hookless alloy, 30mm inner width, tubeless ready
Vorderradnabe	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Hinterradnabe	Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h
Speichen	DT Swiss Industry
Vorderreifen	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Hinterreifen	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Schläuche	Standard, Presta Valve
Sattelstütze	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4: 170mm, S5/S6: 190mm
Sattelstützklemme	Alloy, 38.6mm
Sattel	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Motor	Specialized 1.2 SL Custom Rx Trail Tuned Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Akku	Specialized SL1-320, fully integrated, 320Wh
Ladegerät	Custom charger, 48V System w/ SL system charger plug
Kabelbaum	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Gewicht	20.26 kg (Größe: S4)