


2025 ELYTE EVO





Our mission is simple: make
the best riding bikes on Earth.

whytebikes.com/total-geometry



Confidence by design



ELyte *EVO*

Lightweight, full-power, full-torque eMTB trail

Introducing ELYte EVO: the next step in the evolution of our ELYte range. Lightweight, full-power, full-torque – all the time – so you can make the most of your precious time, every ride.

ELyte EVO: time saver, fun maker.



Elyte EVO Stag Works

Full-power, lightweight eMTB trail



[New model]
[T-type spec]



Lightweight, full-power, full-torque – all of the time.
Introducing our all-new Elyte EVO Stag Works: a lightweight chassis combined with Bosch's 85Nm torque, 600W peak power CX motor that delivers you more runs, more grins, and more fun, every ride. Elyte EVO Stag Works: head turning, mind blowing.

E-bike motor	Bosch Performance Line CX (Smart System) Drive Unit with 85Nm maximum torque, 600W of peak power and 250W of nominal power. Features four power mode settings including Tour+ and eMTB. Also includes Connect Module.
E-bike display	Bosch System controller mounted within the top tube, paired with the discrete bar mounted Mini Remote. Also connects to the Bosch eBike Flow smartphone app to give you even more insight and control at your fingertips.
E-bike battery	Bosch Compact PowerTube 400Wh, integrated within the downtube of the frame at the lowest point for stability and control. Also comes with the external, removable 250Wh Power-More range extender to deliver a combined 650Wh of battery capacity.
E-bike battery charger	Charger 4A (230V)
Shock stroke & sag	50mm/14mm
Reducer bush widths	25mm
Eye to eye length	210mm
Weight	TBC

Size	Reach mm	Stack mm	Head angle degree°	Seat angle degree°	BB height mm
S	431	628.7	64.6 (64)	77.5	341.9 (333.9)
M	456	640.5	64.6 (64)	77.3	341.9 (333.9)
L	481	652.3	64.6 (64)	77.1	341.9 (333.9)
XL	506	663.2	64.6 (64)	76.9	341.9 (333.9)

Size	Wheelbase mm	Rear centre mm	Standover height mm	Seat tube mm	Head tube mm
S	1211.6	450.4	741	395	114
M	1242.1	450.4	741	420	127
L	1272.6	450.4	741	445	140
XL	1302.7	450.4	741	470	152

Sku part code	WELEVOSW(size)V1-1
Sizes available	S, M, L, XL
Colour	Gloss ruby red with black fade
Frame	Uni-directional carbon mainframe and seatstays, tapered head tube, ISCG 2 guide mounts, internal cable routing, Shape.it Link V2 and 12mm x 148mm Boost dropouts
Fork	Fox Float 36 Factory Series 29in, 150mm travel, 44mm offset, Grip X2 damper, tapered steerer, 110mm x 15mm Kabolt axle
Rear shock	Fox Float X Factory Series, EVOL, lock out, 210mm x 50mm, custom tuned for Whyte
Headset	FSA No. 69/56/SRS, 1-1/8in upper and 1.5in lower with sealed angular contact bearing (ACB) cartridge bearings, with side entry internal routing
Rear hub	Hope Pro 5, six bolt, 12mm x 148mm Boost spacing, XD driver, 32 hole
Front hub	Hope Pro 5, six bolt, 15mm x 110mm Boost spacing, 28 hole
Spokes	DT Swiss Elemental
Rims	DT HX531, 30mm internal
Tyres	Maxxis Assegai WT, TR, 29in x 2.5in 120TPI, EXO+ sidewall protection, 3C MaxxGrip, dual compound, folding bead, front; Maxxis Minion DHR 2 WT, TR, 27.5in x 2.5in 120TPI, Double Down casing, 3C MaxxTerra, dual compound, rear
Shift levers	SRAM AXS Pod, right, MMX, 12 speed
Front derailleur	N/A
Rear derailleur	SRAM XO T-Type AXS, 12 speed
Cassette	SRAM XS 1295, T-Type, 10-52T, 12 speed
Chain	SRAM XO T-Type, 12 speed
Crankset	Hope E-Bike cranks, 155mm length, Bosch mounting, 36T chainring T-type
Bottom bracket	N/A
Seatpost	Whyte Drop.it II Adjust, 30.9mm (sizes S/M 140-170mm travel; sizes L/XL 170-200mm travel), MMX paddle remote lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Race Face ERA Carbon, 20mm rise, 35mm bar bore, 800mm wide
Stem	Whyte Trail full CNC, 32mm extension, 35mm bar bore
Grips	Whyte Enduro lock-on
Front brakes	Hope Tech4 V4, four piston hydraulic, 200mm diameter floating disc rotor
Rear brakes	Hope Tech4 V4, four piston hydraulic, 200mm diameter floating disc rotor
Brake levers	Hope Tech 4
Pedals	Fibre reinforced composite platform




Elyte EVO Stag Works

Full-power, lightweight eMTB trail



[New model]
[T-type spec]



Lightweight, full-power, full-torque – all of the time.
Introducing our all-new Elyte EVO Stag Works: a lightweight chassis combined with Bosch's 85Nm torque, 600W peak power CX motor that delivers you more runs, more grins, and more fun, every ride. Elyte EVO Stag Works: head turning, mind blowing.

E-bike motor	Bosch Performance Line CX (Smart System) Drive Unit with 85Nm maximum torque, 600W of peak power and 250W of nominal power. Features four power mode settings including Tour+ and eMTB. Also includes Connect Module.
E-bike display	Bosch System controller mounted within the top tube, paired with the discrete bar mounted Mini Remote. Also connects to the Bosch eBike Flow smartphone app to give you even more insight and control at your fingertips.
E-bike battery	Bosch Compact PowerTube 400Wh, integrated within the downtube of the frame at the lowest point for stability and control. Also comes with the external, removable 250Wh Power-More range extender to deliver a combined 650Wh of battery capacity.
E-bike battery charger	Charger 4A (230V)
Shock stroke & sag	50mm/14mm
Reducer bush widths	25mm
Eye to eye length	210mm
Weight	TBC

Size	Reach mm	Stack mm	Head angle degree °	Seat angle degree °	BB height mm
M	456	640.5	64.6 (64)	77.3	341.9 (333.9)
L	481	652.3	64.6 (64)	77.1	341.9 (333.9)
XL	506	663.2	64.6 (64)	76.9	341.9 (333.9)

Size	Wheelbase mm	Rear centre mm	Standover height mm	Seat tube mm	Head tube mm
M	1242.1	450.4	741	420	127
L	1272.6	450.4	741	445	140
XL	1302.7	450.4	741	470	152

Sku part code	WELEVOSW(size)V1-2
Sizes available	M, L, XL
Colour	Gloss blurple fade
Frame	Uni-directional carbon mainframe and seatstays, tapered head tube, ISCG 2 guide mounts, internal cable routing, Shape.it Link V2 and 12mm x 148mm Boost dropouts
Fork	Fox Float 36 Factory Series 29in, 150mm travel, 44mm offset, Grip X2 damper, tapered steerer, 110m x 15mm Kabolt axle
Rear shock	Fox Float X Factory Series, EVOL, lock out, 210mm x 50mm, custom tuned for Whyte
Headset	FSA No. 69/56/SRS, 1-1/8in upper and 1.5in lower with sealed angular contact bearing (ACB) cartridge bearings, with side entry internal routing
Rear hub	Hope Pro 5, six bolt, 12mm x 148mm Boost spacing, XD driver, 32 hole
Front hub	Hope Pro 5, six bolt, 15mm x 110mm Boost spacing, 28 hole
Spokes	DT Swiss Elemental
Rims	DT HX531, 30mm internal
Tyres	Maxxis Assegai WT, TR, 29in x 2.5in 120TPI, EXO+ sidewall protection, 3C MaxxGrip, dual compound, folding bead, front; Maxxis Minion DHR 2 WT, TR, 27.5in x 2.5in 120TPI, Double Down casing, 3C MaxxTerra, dual compound, rear
Shift levers	SRAM AXS Pod, right, MMX, 12 speed
Front derailleur	N/A
Rear derailleur	SRAM XO T-Type AXS, 12 speed
Cassette	SRAM XS 1295, T-Type, 10-52T, 12 speed
Chain	SRAM XO T-Type, 12 speed
Crankset	Hope E-Bike cranks, 155mm length, Bosch mounting, 36T chainring T-type
Bottom bracket	N/A
Seatpost	Whyte Drop.it II Adjust, 30.9mm (sizes S/M 140-170mm travel; sizes L/XL 170-200mm travel), MMX paddle remote lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Race Face ERA Carbon, 20mm rise, 35mm bar bore, 800mm wide
Stem	Whyte Trail full CNC, 32mm extension, 35mm bar bore
Grips	Whyte Enduro lock-on
Front brakes	Hope Tech4 V4, four piston hydraulic, 200mm diameter floating disc rotor
Rear brakes	Hope Tech4 V4, four piston hydraulic, 200mm diameter floating disc rotor
Brake levers	Hope Tech 4
Pedals	Fibre reinforced composite platform



Elyte EVO RS

Lightweight eMTB trail



New model
T-type spec



Lightweight, full-power, full-torque - all of the time

Introducing our all-new Elyte EVO RS: a lightweight chassis combined with Bosch's 85Nm torque, 600W peak power CX motor that delivers you more runs, more grins, and more fun, every ride. Elyte EVO RS: head turning, mind blowing.

E-bike motor	Bosch Performance Line CX (Smart System) Drive Unit with 85Nm maximum torque, 600W of peak power and 250W of nominal power. Features four power mode settings including Tour+ and eMTB.
E-bike display	Bosch System controller mounted within the top tube, paired with the discrete bar mounted Mini Remote. Also connects to the Bosch eBike Flow smartphone app to give you even more insight and control at your fingertips.
E-bike battery	Bosch Compact PowerTube 400Wh, integrated within the downtube of the frame at the lowest point for stability and control. Also comes with the external, removable 250Wh Power-More range extender to deliver a combined 650Wh of battery capacity.
E-bike battery charger	Charger 4A (230V)
Shock stroke & sag	50mm/14mm
Reducer bush widths	25mm
Eye to eye length	210mm
Weight	TBC

Size	Reach mm	Stack mm	Head angle degree °	Seat angle degree °	BB height mm
S	431	628.7	64.6 (64)	77.5	341.9 (333.9)
M	456	640.5	64.6 (64)	77.3	341.9 (333.9)
L	481	652.3	64.6 (64)	77.1	341.9 (333.9)
XL	506	663.2	64.6 (64)	76.9	341.9 (333.9)

Size	Wheelbase mm	Rear centre mm	Standover height mm	Seat tube mm	Head tube mm
S	1211.6	450.4	741	395	114
M	1242.1	450.4	741	420	127
L	1272.6	450.4	741	445	140
XL	1302.7	450.4	741	470	152

Skus part code WELEVORS(size)V1

Sizes available	S, M, L, XL
Colour	Gloss deep purple with black
Frame	Uni-directional carbon mainframe and seatstays, tapered head tube, ISCG 2 guide mounts, internal cable routing, Shape.it Link V2 and 12mm x 148mm Boost dropouts
Fork	RockShox Lyrik Select+, 150mm travel, DebonAir+, Charger 3.1 Damper, Fast Black coating, tapered steerer, 110 x 15mm Boost
Rear shock	RockShox Deluxe Select+ RT, DebonAir, Fast Black coating, adjustable rebound and two position compression adjustment, custom tuned for Whyte
Headset	FSA No. 69/56/SRS, 1-1/8in upper and 1.5in lower with sealed angular contact bearing (ACB) cartridge bearings, with side entry internal routing
Rear hub	Alloy, light assist e-bike specific, double sealed cartridge bearings, 12mm x 148mm Boost spacing, 32 hole
Front hub	Alloy, double sealed cartridge bearings, 15mm x 110mm Boost spacing, 28 hole
Spokes	DT Swiss Elemental
Rims	WTB ST Tough, 30mm internal width
Tyres	Maxxis Minion DHF, EXO TR MaxxGrip 29in x 2.5in front; Maxxis Dissector, EXO+ TR MaxxTerra 29in x 2.4in, rear
Shift levers	SRAM AXS Pod, right, MMX, 12 speed
Front derailleur	N/A
Rear derailleur	SRAM S1000 T-Type AXS, 12 speed
Cassette	SRAM XS 1270, T-Type, 10-52T, 12 speed
Chain	SRAM GX T-Type, 12 speed
Crankset	Whyte 155mm ISIS arms, SRAM direct mount 36T chainring, T-Type
Bottom bracket	N/A
Seatpost	TranzX +RAD 30.9mm, adjustable size-specific drop (sizes S: 125mm travel; size M: 150mm travel; size L: 170mm travel; size XL: 200mm travel)
Seat	Whyte Custom
Bar	Whyte Custom 6061 alloy, 30mm rise, 35mm bar bore, 800mm wide
Stem	Whyte Trail full CNC, 32mm extension, 35mm bar bore
Grips	Whyte Enduro lock-on
Front brakes	SRAM Code Bronze Stealth, four piston hydraulic, 200mm diameter disc rotor
Rear brakes	SRAM Code Bronze Stealth, four piston hydraulic, 200mm diameter disc rotor
Brake levers	SRAM Code Bronze Stealth
Pedals	Fibre reinforced composite platform